



THOMAS MAXWELL

ARTISAN LEATHERS

LAVELLE 12 colours

Lavelle is a surface grain leather, lightly buffed and finished with oils and natural waxes, then lightly pigmented to achieve its silky two tone dimension. Colour selections are designed to enhance the most sophisticated living space for use in both heavy domestic and general commercial applications.

Thomas Maxwell Leather Quality Guarantee

For a period of three years, for both domestic and commercial applications, we guarantee to replace any leather which is found to be faulty as a result of manufacturing defect and which has been used in accordance with our performance ratings and care instructions.

This Guarantee is additional to all statutory rights and remedies that are available to our customers under Consumer Law.

Colour Variations

All leather colours will be supplied within commercial shade tolerances, however some natural colour variations may occur from batch to batch. If colour matching is critical please contact our sales office.

Available from
Warwick Fabrics:

AUSTRALIA
T: 1300 787 888
F: +61 (0) 3 9416 1060
info@warwick.com.au
www.warwick.com.au

NEW ZEALAND
T: +64 (0) 9 477 3080
F: +64 (0) 9 479 6313
info@warwick.co.nz
www.warwick.co.nz

Specifications		Lavelle		
Performance		Heavy Domestic & General Commercial		
Warranty		3 Years		
Care		Should include the application of commercially available leather care products, used in accordance with care label instructions.		
Animal Source		Bovine Cattlehide		
Origin		Italian with Selected European Breed		
Type		Surface grain, lightly buffed and finished with oils and natural waxes, lightly pigmented.		
Thickness		0.9 - 1.1mm		
Average Hide Size		5m2		
Rubfastness (grey scale grade) EN ISO 11640 (SLF450)	Dry 500	Marring	Transfer	Results
	Wet 250	4/5	4/5	Pass
	Sweat 80	4/5	4	Pass
		4/5	4	Pass
Fastness to Light (Blue wool rating) EN ISO 105:B02 (SLF 402)		>5		Pass
Finish Adhesion (N/cm) EN ISO 11644 (IUF470)	Along	5.5		Pass
	Across	6.2		Pass
	Average	5.8		Pass
Flex Resistance (50,000 cycles) EN ISO 5402 (IUF20)		No cracks at 50,000 cycles		Pass
Tear Strength (N) EN ISO 3377-1 (IUP 8)	Along	25		Pass
	Across	23		Pass
	Average	24		Pass
pH EN ISO 4045 (IUC 11)		4.4		Pass
Formaldehyde ISO 17226-1		8ppm		Pass
Flammability IMO RESOLUTION A.652 (16)		Pass		
Flammability AS1530.3		Ignitability Index	15	
		Spread of Flame Index	0	
		Heat Evolved Index	3	
		Smoke Developed Index	5	

Please Note: Median test results displayed based off results from light, medium, & dark hides.